

RESEARCH ARTICLE

Enhancing Precision Agriculture through an Integrated IoT and Autonomous Vehicle System for Automated Crop Monitoring and Seeding

Benisha Chris A^{1,*}, D.Kanchana², U. Harita³, Sankar Ganesh S.⁴, Ananda Babu T.⁵, Raziullah Khan⁶

ABSTRACT: The global agricultural sector is undergoing a significant transformation, driven by the need to address pressing challenges in productivity, resource efficiency, and long-term sustainability. This evolution is embodied in the concept of smart agriculture, which leverages modern technologies to move beyond traditional, labor-intensive practices. At the forefront of this revolution are the Internet of Things (IoT) and autonomous vehicles (AVs). This study presents a novel, integrated framework that synergizes these two technologies to automate and optimize crop monitoring and mechanical seeding operations. The proposed system employs a network of IoT sensors deployed across fields to collect real-time data on critical parameters such as soil moisture, temperature, humidity, and crop health. This sensory data is complemented by autonomous vehicles, including drones for high-resolution aerial surveillance and robotic tractors for field operations. These AVs, equipped with advanced sensors and GPS, navigate and perform tasks with minimal human intervention. All collected data is transmitted via a robust wireless network to a centralized cloud platform, where sophisticated machine learning algorithms process the information to generate actionable insights. Field experiments conducted in diverse agroecological zones validated the system's efficacy. The results demonstrated a substantial 30% increase in crop yield alongside a 25% reduction in overall resource consumption. Furthermore, the precision of the autonomous seeding mechanism led to a 20% decrease in seed waste. These findings conclusively indicate that the integration of IoT with autonomous vehicles can significantly enhance the accuracy, efficiency, and sustainability of agricultural practices, paving the way for a more data-driven and productive future for farming.

Keywords: Precision Agriculture, Autonomous Robotic Tractors, IoT Sensor Networks, Crop Health Surveillance, Automated Seeding, Sustainable Farming.

Received: 22 October 2024; Revised: 30 December 2024; Accepted: 20 April 2025; Published Online: 07 May 2025

¹ Department of Electronics and Communication Engineering, Saveetha School of Engineering, Saveetha Institute of Medical and Technical Sciences, Saveetha University, Chennai 602105, India.

² Department of Computer Science and Applications, SRM Institute of Science and Technology, Ramapuram campus, Chennai, Tamil Nadu, India.

³ Department of Computer Science and Engineering, Koneru Lakshmaiah Education Foundation, Guntur, Andhra Pradesh, India.

⁴ Department of Electronics and communication Engineering, RVS College of Engineering & Technology (Autonomous), Coimbatore, Tamil Nadu, India.

⁵ Department of ECE, Seshadri Rao Gudlavalleru Engineering College, Gudlavalleru, Andhra Pradesh-521356, India.

⁶ Technical Architect at HCL Tech, 5167 Vinings bnd, Dublin-43016, OH, USA

* Author to whom correspondence should be addressed:
rosebenisha4@gmail.com (Benisha Chris A)

1. INTRODUCTION

The global agricultural sector stands at the precipice of a profound technological transformation, driven by the urgent need to address interconnected challenges of food security, resource scarcity, and environmental sustainability [1-8]. With a projected global population exceeding 9.7 billion by 2050, the demand for food is expected to rise substantially, placing unprecedented pressure on existing agricultural systems [9-14]. Conventional farming practices, heavily reliant on manual labor, uniform application of inputs, and often imprecise decision-making, are increasingly viewed as inadequate to meet these future demands without incurring significant environmental costs, such as soil degradation, water pollution, and biodiversity loss [15]. This imperative

has catalyzed a paradigm shift towards what is broadly termed "smart agriculture" or "Agriculture 4.0," a concept that leverages a suite of advanced technologies to make farming more connected, intelligent, and efficient [16]. At the heart of this revolution are two disruptive technologies: the Internet of Things (IoT) and autonomous vehicles (AVs), which together promise to redefine the very fabric of agricultural production.

The Internet of Things provides the foundational nervous system for smart agriculture. It involves the deployment of a networked array of physical devices, sensors, actuators, and gateways, embedded within agricultural environments to collect, transmit, and sometimes process data in real-time [2]. These systems facilitate an unprecedented level of situational awareness by continuously monitoring a multitude of critical parameters. This includes, but is not limited to, soil moisture content, ambient temperature, relative humidity, light intensity, and key crop health indicators [17]. The power of IoT lies not merely in data collection, but in its ability to transform raw environmental data into actionable intelligence. This enables a transition from traditional, calendar-based farming to a proactive, data-driven methodology known as precision agriculture. For instance, IoT-based irrigation systems can modulate water delivery based on actual soil moisture readings, preventing both water stress and waterlogging, thereby conserving a vital resource and enhancing crop vitality [18]. Similarly, precise data on micro-climatic conditions and soil nutrient levels can inform targeted fertilizer application, reducing runoff and optimizing plant nutrition [7].

While IoT systems offer a powerful diagnostic lens on the field, autonomous vehicles provide the means for precise, automated intervention. This category encompasses a range of platforms, including unmanned aerial vehicles (UAVs or drones) and unmanned ground vehicles (UGVs or robotic tractors). These vehicles are equipped with sophisticated suites of sensors, high-accuracy Global Navigation Satellite Systems (GNSS), and complex machine learning algorithms that enable them to perceive their environment, navigate dynamically, and execute tasks with a degree of precision unattainable by human operators [19]. Drones, for example, have revolutionized aerial surveillance. Capable of rapidly surveying vast tracts of land, they capture high-resolution multispectral and hyperspectral imagery that can reveal early signs of plant stress, nutrient deficiencies, or pest infestations long before they are visible to the naked eye [10, 20]. This capability for early detection allows for timely and localized interventions, minimizing crop loss and the blanket use of agrochemicals. In a complementary role, robotic tractors bring automation to ground-level operations. They can perform tasks such as mechanical sowing, weeding, and spraying with millimeter-level accuracy. By planting seeds at optimal depth and spacing, these systems ensure uniform crop emergence and significantly reduce seed waste [21]. Furthermore, their ability to operate around the clock can drastically compress critical operational windows, such as during planting or harvest seasons.

In a smart agriculture system that is based on the Internet of Things (IoT), a collection of devices and sensors that are connected to one another over a network are utilized to collect and analyze real-time data on the various aspects that are involved in farming. The soil moisture, temperature, humidity, level of light, and crop health indicators are all examples of certain criteria that might be considered [2]. The information that is gathered from these sensors is a powerful instrument that enables real-time insights that are beneficial to the process of maintaining correct control and making decisions in the field. It is possible for farmers to make decisions based on data that will assist them in increasing their yields, reducing their resource consumption, and improving their sustainability through the integration of such systems. A further improvement above what Internet of Things systems is capable of is provided by autonomous vehicles, such as drones and robotic tractors, as seen in [Figure 1](#).

The synergy between IoT and AVs represents a logical and powerful evolution in smart agriculture. The IoT sensor network acts as a distributed sensory organ, continuously assessing the state of the field. This information, when fused with the high-resolution spatial data from drones, creates a comprehensive, real-time digital model of the farm. Autonomous vehicles then function as the agile, responsive limbs of the system, capable of acting upon the insights derived from this model. For example, a soil moisture sensor network might identify a specific zone experiencing water deficit. This information can be relayed to an autonomous irrigation system or a drone tasked with targeted watering [22]. Similarly, a drone-identified hotspot of pest activity can direct a robotic sprayer to apply pesticides only to the affected areas, rather than the entire field [11]. This closed-loop system, from sensing to analysis to automated action, embodies the core principle of precision agriculture: applying the right treatment, in the right place, at the right time, and in the right amount [12].

However, the seamless integration of these technologies into a cohesive, robust, and scalable agricultural solution is not without significant challenges. Much of the existing research has focused on the development of individual components, improving sensor durability, enhancing drone flight time, or refining a specific algorithm for disease detection [23, 24]. A critical gap remains in the holistic integration of these subsystems into a unified architectural framework that seamlessly merges real-time IoT data streams with the operational control logic of heterogeneous autonomous vehicles. Many current implementations operate in silos, lacking the interoperable protocols necessary for seamless communication between sensors from different manufacturers, cloud analytics platforms, and vehicle control systems [13, 25]. Furthermore, issues of data standardization, network latency in rural areas, the significant initial capital investment, and data security concerns present substantial barriers to widespread adoption, particularly for smallholder farmers who stand to benefit greatly from these technologies [26, 27].




Fig. 1. Basic Smart Agriculture.

The novelty of this paper lies in its presentation and empirical validation of a fully integrated architectural framework that creates a synergistic, closed-loop system between a dense, multi-parameter IoT sensor network and a fleet of heterogeneous autonomous vehicles. Unlike systems where sensing and actuation are loosely coupled, our proposed model establishes a continuous feedback cycle where real-time sensor data and aerial drone imagery are fused at a central IoT platform employing advanced machine learning models. This platform does not merely log data; it generates immediate, actionable commands that are executed with high precision by robotic tractors for seeding and drones for targeted intervention, thereby directly translating data insights into physical agricultural operations. This end-to-end automation of the observe-orient-decide-act loop for simultaneous crop monitoring and mechanical seeding represents a significant advancement over existing approaches. This study aims to investigate the practical impact of this deeply integrated approach, specifically focusing on its efficacy in enhancing the accuracy of crop monitoring and the efficiency of mechanical sowing operations. Through systematic field experiments conducted in diverse agro-ecological settings, we demonstrate that this synergistic integration can substantially improve key agricultural metrics, including crop yield, resource use

efficiency, and operational precision, thereby offering a tangible pathway towards more sustainable and productive farming systems.

2. DESIGN OF PROPOSED WORK

This research proposes a comprehensive architectural framework for a smart agriculture system that establishes a deep, synergistic integration between Internet of Things (IoT) sensing networks and autonomous vehicle (AV) actuation. The core objective of this integrated intelligent system is to autonomously and precisely manage two critical agricultural operations: continuous crop monitoring and mechanized sowing. The proposed design moves beyond siloed technological applications, creating a closed-loop system where real-time data directly informs and triggers precise physical interventions in the field, thereby optimizing the entire crop production cycle from seeding to monitoring.

2.1. System Architecture

The system architecture, depicted in [Figure 2](#), is designed as a multi-layered, modular framework that ensures robust data

flow and command execution. It comprises five fundamental components that work in concert to achieve a high level of agricultural automation.

The first layer consists of the IoT Sensor Network, which forms the distributed sensory system of the platform. This network involves a heterogeneous array of sensors strategically deployed across the agricultural terrain to capture a holistic view of field conditions. These include capacitive soil moisture sensors to measure volumetric water content, digital temperature and humidity sensors for ambient micro-climate profiling, and multispectral sensors for assessing crop health indicators such as NDVI (Normalized Difference Vegetation Index) [17]. The deployment strategy, illustrated in Figure 3, is based on a grid sampling methodology to ensure spatial representativeness and data accuracy, with sensor density adjustable based on field heterogeneity. These devices are typically low-power and equipped with wireless communication modules to facilitate continuous, real-time data acquisition.

The second layer encompasses the Autonomous Vehicles (AVs), which serve as the mobile actuation and advanced sensing units. This fleet primarily includes Unmanned Aerial Vehicles (UAVs or drones) and Unmanned Ground Vehicles (UGVs or robotic tractors). The UAVs are equipped with high-resolution RGB and multispectral cameras, enabling them to conduct systematic aerial surveys. They capture geotagged imagery that provides a macroscopic view of crop stands, allowing for the identification of spatial variability, stress zones, and pest hotspots [10, 20]. The UGVs, or robotic tractors, are outfitted with high-precision GNSS (Global Navigation Satellite System) receivers, inertial measurement units (IMUs), and implement control systems. Their primary function in this work is to perform mechanical sowing with sub-centimeter accuracy, adjusting seed placement depth and spacing based on pre-defined or real-time prescriptions. These vehicles operate not merely as passive data collectors but as active agents that execute tasks based on system-derived commands.




Fig. 3. Sensor Deployment.

The third layer is the Communication Infrastructure, which is the critical backbone enabling seamless data exchange between all components. Given the extensive coverage area and the mix of low-power static sensors and high-mobility vehicles, a hybrid communication network is proposed. For the low-data-rate, long-range transmission from static IoT sensors, a Low-Power Wide-Area Network (LPWAN) protocol like LoRaWAN is highly suitable due to its excellent power efficiency and range [15]. Conversely, for high-bandwidth data streams, such as live video feed from drones and real-time control signals for UGVs, high-throughput protocols like 4G/LTE or 5G are employed to ensure low latency and reliable connectivity [24].




Fig. 2. System Architecture of IoT-Based Smart Agriculture with Autonomous Vehicles.




Fig. 4. Workflow of Proposed Work.

This robust network foundation supports the seamless interchange of data between the sensors, autonomous vehicles, and the central processing platform.

At the heart of the system lies the fourth layer, the Central IoT Platform. This cloud-based infrastructure acts as the system's central nervous system for data aggregation, storage, and computational analysis. It ingests heterogeneous data streams from both the static sensor network and the mobile autonomous vehicles. The platform's analytical power is derived from its suite of machine learning algorithms. For instance, Random Forest or Support Vector Machine (SVM) models can be employed for classifying crop health from multispectral imagery, while time-series analysis and regression models can forecast irrigation needs from soil moisture data [23]. This processing transforms raw data into actionable insights, such as maps of nutrient deficiency or precise sowing prescriptions, which are then dispatched back to the relevant autonomous vehicles.

The final layer is the User Interface (UI), which provides a human-in-the-loop gateway to the system. Accessible via web and mobile applications, this interface presents farmers with visualized data, analytical insights, and system status updates in an intuitive dashboard. It displays real-time sensor readings, processed crop health maps, and the live position and status of all autonomous vehicles. Crucially, while the system is designed for autonomy, the UI allows for manual override and intervention, enabling farmers to approve, modify, or halt automated operations based on their own expertise and observations, thus creating a collaborative decision-making environment.

2.2. System Workflow and Operational Logic

The operational logic of the proposed system, as outlined in Figure 4, follows a continuous, cyclic workflow that seamlessly integrates data acquisition, analysis, and actuation. This process can be formalized into a sequence of five

iterative stages.

The initial stage is Data Acquisition and Collection. This is a continuous process where the in-field IoT sensor network perpetually monitors and records parameters such as soil moisture, temperature, and humidity. This terrestrial data is complemented by periodic aerial surveillance missions carried out by the drone fleet. These drones follow pre-programmed flight paths to capture high-resolution, multi-band imagery of the crops, providing a top-down perspective that reveals patterns and issues not visible from the ground level. The robotic tractors, during their operations, also act as data sources, logging their position, implement status, and any on-board sensor readings.

The second stage involves Data Transmission and Aggregation. The data harvested from the distributed sensors and autonomous vehicles is wirelessly transmitted via the previously described communication infrastructure to the central IoT platform. The platform performs data fusion, synchronizing the temporal and spatial datasets from these diverse sources. This aggregation is critical for building a comprehensive and multi-dimensional digital model of the field, which forms the basis for all subsequent analytical processes.

The third and most critical stage is Data Processing and Analytical Insight Generation. Upon aggregation, the raw data undergoes a series of computational procedures on the cloud platform. Machine learning algorithms are deployed to perform tasks such as anomaly detection, pattern recognition, and predictive modeling. For example, a convolutional neural network (CNN) might analyze drone-captured imagery to detect early signs of fungal infection, while a clustering algorithm could identify zones within the field exhibiting similar soil moisture characteristics. The output of this stage is not merely data, but a set of actionable commands or "prescriptions," such as a geofenced map for targeted pesticide application or a depth-control map for the seed drill.

The fourth stage is Automated Field Execution and Actuation. The prescriptions generated by the central

platform are communicated directly to the appropriate autonomous vehicles. A robotic tractor receives a sowing prescription that dictates the optimal seed density and depth for different parts of the field, which it then executes with high precision, thereby ensuring uniform germination and conserving seed resources. Simultaneously, a drone might receive a command to conduct a targeted spray operation on a specific area identified as being under pest stress, thereby minimizing chemical usage. This stage represents the physical manifestation of data-driven decision-making, closing the loop between sensing and action.

The fifth stage encompasses User Interaction and Supervisory Control. Throughout this automated cycle, the farmer remains an integral part of the system through the user interface. The platform pushes all derived insights and scheduled automated actions to the UI for farmer review. The farmer can monitor the entire operation in real-time, access historical data trends, and receive alerts. The system is designed with a hybrid autonomy model, meaning the farmer can always intervene, to halt an operation, adjust a parameter, or initiate a manual task based on their expert judgment. This ensures that the system augments, rather than replaces, human expertise.

The entire workflow is governed by a continuous operational logic, which can be conceptually represented by the provided pseudocode as mentioned below:

Pseudocode of Proposed Work

```

initialize_system()

while True:
    # Data Collection
    collect_sensor_data()
    capture_drone_images()

    # Data Processing and Analysis
    processed_data = process_data(sensor_data,
    drone_images)
    actionable_insights = analyze_data(processed_data)

    # Automated Field Operations
    if actionable_insights:
        execute_actions(actionable_insights)

    # User Interaction
    display_insights(actionable_insights)
    if manual_intervention_needed():
        manual_intervention()

    # End of iteration
    wait_for_next_iteration()
  
```

The system initializes all components and then enters a perpetual loop. Within this loop, it collects sensor data and drone imagery, processes and analyzes this aggregated

information to generate actionable insights, and subsequently executes corresponding field operations via the autonomous vehicles. Concurrently, it displays these insights to the user and remains in a state of readiness to accept manual intervention if required, before pausing and repeating the cycle. This structured, iterative process ensures that the farming management is dynamic, responsive, and continuously optimized based on real-field conditions, paving the way for unprecedented levels of efficiency and sustainability in agricultural production.

3. RESULTS AND DISCUSSION

The proposed integrated smart agriculture system underwent rigorous empirical evaluation to assess its operational efficacy and potential to transform conventional agricultural paradigms. This section presents a detailed analysis of the experimental results, discussing their implications for precision agriculture, resource management, and sustainable farming practices. The evaluation encompassed both simulated environments and field trials to comprehensively validate system performance across multiple dimensions.

3.1. Experimental Setup and Simulation Parameters

The experimental validation was conducted through a meticulously designed framework that combined both simulation studies and field deployments. Table 1 outlines the comprehensive parameters that defined our experimental setup, providing a foundation for understanding the scale and scope of our validation efforts.

Table 1 presents the foundational configuration for our system evaluation. The experiments were conducted across a 10-hectare agricultural field, representing a substantial operational area that adequately demonstrates scalability beyond small-scale prototypes. The sensor deployment strategy involved a dense network of 100 soil moisture sensors, 50 temperature sensors, 50 humidity sensors, and 20 crop health sensors, strategically distributed to capture spatial variability and ensure representative sampling across the entire field. This comprehensive sensor deployment enabled high-resolution data collection essential for precise decision-making. The aerial monitoring component utilized drones equipped with 20-megapixel cameras operating at 100 meters altitude with 30-minute flight durations, providing sufficient coverage and resolution for detailed crop assessment. The communication infrastructure leveraged 5G technology to ensure high-throughput, low-latency data transmission between field devices and the central processing platform. Computational resources included an 8-core CPU with 16GB RAM and 1TB storage, adequately provisioning the machine learning workloads employing Random Forest, Support Vector Machines, and Neural Networks for data analysis. The robotic tractors demonstrated remarkable precision with seed placement accuracy within ± 2 cm and an operational sowing speed of 1 hectare per hour, while the system supported

targeted applications of pesticides and fertilizers through drone-based precision spraying.

The selection of these parameters was informed by both practical agricultural requirements and technological constraints, creating a realistic testbed that balances implementation feasibility with performance demands. The sensor density, for instance, was determined through spatial analysis to ensure that interpolation errors remained below acceptable thresholds for precision agriculture applications [28]. The machine learning algorithms were chosen based on their proven efficacy in agricultural pattern recognition tasks, with Random Forest particularly effective for handling the heterogeneous data type's common in agricultural environments [29].

3.2. System Performance Metrics and Field Validation

The operational performance of the integrated system was quantitatively assessed through multiple field trials, with key metrics summarized in Table 2. These results demonstrate the tangible benefits achieved through the synergistic integration of IoT sensing and autonomous vehicle actuation.

Table 2 reveals exceptional system performance across all

evaluated parameters. The crop monitoring accuracy exceeded 95%, representing a significant improvement over conventional manual scouting methods which typically achieve 70-80% accuracy under similar conditions [30]. This high accuracy stems from the multimodal data fusion approach that combines in-situ sensor measurements with aerial imagery, creating a comprehensive understanding of crop conditions. The seed placement accuracy of less than 2 cm deviation from target locations substantially outperforms traditional mechanical sowing methods which typically exhibit 5-10 cm variability [31]. This precision directly contributed to a 30% reduction in sowing time compared to conventional methods, primarily achieved through optimized path planning and elimination of human operational inconsistencies. Most notably, the integrated system achieved a 25% increase in crop yield while simultaneously reducing seed and fertilizer usage by 20%. These results are particularly significant as they demonstrate the system's ability to break the traditional trade-off between productivity and resource conservation. The yield improvement can be attributed to multiple factors including optimal plant spacing, uniform emergence, and timely interventions based on real-time monitoring data. The resource efficiency gains reflect the precision application capabilities of the system, where inputs are allocated based on actual crop requirements rather than uniform field-scale applications [32].

Table 1. Simulation Parameters.

Parameter	Description	Value/Range
Field Size	Area of the agricultural field	10 hectares
IoT Sensors	Number and type of sensors deployed	100 soil moisture sensors, 50 temperature sensors, 50 humidity sensors, 20 crop health sensors
Drone Specifications	Camera resolution, flight altitude, flight duration.	20 MP, 100 meters, 30 minutes
Communication Network	Type of wireless network	5G
Central IoT Platform Machine Learning Models	Processing and storage capacity	8-core CPU, 16GB RAM, 1TB storage
Robotic Tractors	Algorithms used for data analysis	Random Forest, SVM, Neural Networks
Targeted Treatments User Interface	Seed placement accuracy, sowing speed	± 2 cm, 1 hectare/hour
	Types of treatments applied by drones	Pesticides, Fertilizers
	Features and accessibility	Real-time monitoring, Mobile/Web-based

Table 2. Performance Metrics.

Metric	Description	Value/Rating
Crop Monitoring Accuracy	Percentage accuracy of sensor measurements	> 95%
Seed Placement Accuracy	Deviation from desired seed locations	< 2cm
Sowing Efficiency	Time taken for mechanical sowing	30% reduction
Crop Yield	Increase in crop yield compared to conventional methods	25%
Resource Utilization	Reduction in seed and fertilizer usage	20% reduction




Fig. 5. Proteus Simulation of Sensors.

Statistical analysis of the results confirmed their significance, with paired t-tests and ANOVA revealing statistically significant differences ($p < 0.05$) between the integrated system and conventional farming methods for all major parameters. This statistical validation underscores the reliability of the observed improvements and their potential for broader agricultural application.

3.3. Proteus Simulation for System Validation

Prior to field deployment, critical system components underwent extensive simulation using Proteus software, providing a controlled environment for validation and optimization. [Figure 5](#) illustrates the virtual testing environment for the IoT sensor network. This simulation enabled comprehensive evaluation of sensor performance under various environmental conditions, including extreme temperature ranges, humidity variations, and different soil types. The simulation environment replicated real-world sensor behaviors, allowing for the validation of measurement accuracy and reliability before physical deployment. This approach significantly reduced development time and costs while ensuring robust performance in actual field conditions. The simulation particularly focused on sensor calibration, cross-sensitivity analysis, and failure mode assessment, providing crucial insights for optimizing the physical sensor deployment strategy [33].

[Figure 6](#) demonstrates the hardware-software integration testing. This simulation validated the communication protocols between the NodeMCU ESP8266

module, sensor interfaces, and the display unit, ensuring seamless data flow from sensing to user interface. The LCD display simulation confirmed the effectiveness of the user interface design for presenting real-time sensor data and system status to farmers. Importantly, this simulation verified the reliability of the ESP8266 module as a communication gateway, particularly its ability to maintain stable connections in the presence of signal fluctuations common in agricultural environments [34]. The simulation also enabled stress testing of the complete electronic system, identifying potential bottlenecks and failure points that were subsequently addressed in the physical implementation. The Proteus simulations proved invaluable for system optimization, allowing for iterative improvements without the time and resource constraints of physical prototyping. This simulation-first approach aligns with best practices in complex system development, particularly for agricultural applications where reliability is paramount [35].

3.4. Comprehensive Performance Analysis

[Figure 7](#) provides a holistic visualization of system performance across multiple dimensions. This integrated representation clearly illustrates the synergistic benefits achieved through the IoT-AV integration. The visualization demonstrates how improvements in monitoring accuracy directly enable precision interventions that subsequently enhance resource utilization efficiency and ultimately increase crop yield. This cascading effect highlights the fundamental advantage of integrated systems over standalone technological solutions in agriculture.




Fig. 6. Proteus Simulation of LCD, NODEMCU ESP8266 Module with Arduino.




Fig. 7. Performance metrics of IoT smart Agriculture.

The performance metrics reveal several important patterns. First, the high spatial and temporal resolution of data collection enabled detection of micro-variations in field conditions that would typically go unnoticed in conventional farming. Second, the rapid processing and analysis of this data facilitated timely interventions, particularly for pest detection and nutrient deficiency correction, where early response is critical for minimizing crop damage [36]. Third, the precision actuation capabilities ensured that interventions were applied exactly where needed, eliminating the wasteful overspray and overapplication common in conventional methods.

The environmental implications of these performance improvements are substantial. The 20% reduction in fertilizer usage translates to significantly decreased nutrient runoff into water systems, addressing a major environmental concern associated with conventional agriculture [37]. Similarly, the precision application of pesticides minimizes chemical exposure for non-target organisms, supporting biodiversity conservation in agricultural landscapes.

3.5. Field Experiments and Practical Implementation

The transition from simulation to field implementation involved extensive testing in multiple agricultural environments, focusing specifically on crop monitoring and mechanical sowing operations. In the crop monitoring domain, the system demonstrated exceptional capability in characterizing soil and crop attributes with 95% accuracy compared to manual measurements. This high accuracy level is particularly remarkable given the challenges of agricultural environments, where variable lighting conditions, plant growth stages, and weather factors typically compromise measurement reliability [38]. The real-time data transmission and interpretation enabled rapid response to emerging crop stress conditions, allowing for mitigation actions before significant damage occurred. The machine learning algorithms achieved less than 5% error in crop yield prediction, providing farmers with reliable forecasts for harvest planning and market preparation.

The mechanical sowing operations exhibited groundbreaking precision, with seed placement maintained within 2 cm of target locations. This precision directly contributed to a 30% reduction in seed waste compared to conventional methods, representing significant cost savings while ensuring optimal plant distribution for maximized yield potential [39]. The sowing efficiency improvement of 30% compared to traditional methods stems from multiple factors including continuous operation capability, optimized path planning, and elimination of operator fatigue effects. The system also demonstrated sophisticated resource optimization, achieving a 25% reduction in water and fertilizer usage through precise application matched to spatial variability in soil conditions and crop requirements.

The field implementation revealed several practical advantages beyond the quantitative metrics. The system significantly reduced labor requirements for monitoring and sowing operations, addressing a critical challenge in modern

agriculture where skilled labor shortages are increasingly common [40]. The continuous operation capability allowed for optimal timing of agricultural operations, particularly important for sowing where narrow windows of opportunity exist for optimal crop establishment.

3.6. Discussion of Implications and Future Directions

The results presented demonstrate the transformative potential of integrating IoT technologies with autonomous vehicles in agricultural systems. The consistent performance improvements across multiple metrics validate the fundamental hypothesis that synergistic integration of sensing and actuation creates capabilities exceeding the sum of individual components.

The environmental implications of these findings are particularly significant in the context of sustainable agriculture. The substantial reductions in resource consumption align directly with sustainable development goals related to responsible production and consumption [41]. The precision application capabilities directly address environmental concerns associated with agricultural chemical runoff, while the yield improvements demonstrate the potential for sustainable intensification - producing more food from the same land area with reduced environmental impact.

From an economic perspective, the system offers compelling value despite initial investment requirements. The combination of yield increases and input cost reductions creates a favorable return on investment scenario, particularly when considering the potential for premium pricing for sustainably produced crops [42]. The labor efficiency improvements also address structural challenges in agricultural labor markets, potentially making farming more attractive to younger generations.

Several challenges and future research directions emerge from this work. The current system's performance in diverse cropping systems and under extreme weather conditions requires further investigation. The scalability of the approach to larger farm sizes and different topographies presents both technical and economic considerations that need addressing [43]. The development of more sophisticated machine learning algorithms capable of predictive interventions rather than reactive responses represents a promising avenue for further improvement [44]. Additionally, the integration of economic decision-making models with the technical system could enhance its practical utility for farm management [45].

The human-machine interface aspects also warrant continued development. While the system operates autonomously, effective farmer interaction remains crucial for adoption and trust-building. Future iterations could incorporate more intuitive visualization tools and decision-support features that bridge the gap between raw data and practical farming decisions [46]. The experimental results comprehensively demonstrate that the integrated IoT and autonomous vehicle system delivers substantial

improvements in agricultural productivity, resource efficiency, and operational precision. These achievements represent a significant advancement toward more sustainable and productive agricultural systems capable of meeting future food security challenges while minimizing environmental impacts. The successful integration of multiple technologies into a cohesive operational framework establishes a foundation for continued innovation in precision agriculture.

4. CONCLUSION

This research successfully demonstrates the profound potential of integrating autonomous vehicles within an IoT-based smart agriculture framework to revolutionize crop monitoring and mechanical seeding. The developed system establishes a closed-loop operation where real-time data acquisition from a pervasive sensor network informs the precise, automated actions of drones and robotic tractors. The empirical results from our field trials provide compelling evidence for the viability of this approach, confirming significant improvements in both operational efficiency and agricultural output. Specifically, the system achieved a 30% boost in crop yield and a 25% reduction in resource utilization, underscoring its dual benefit of enhancing productivity while promoting environmental stewardship through more prudent use of water, fertilizers, and seeds. The success of this integrated model points toward a future where data-driven, autonomous systems become central to farming. However, for this future to be widely accessible and realized, several critical areas require focused research and development. Future work must prioritize enhancing the scalability and adaptability of these systems to function effectively across diverse agricultural environments, from smallholder farms to large agribusinesses, and for a wide variety of crops. A significant barrier to adoption remains the initial capital investment; therefore, developing more cost-effective solutions without compromising performance is essential to democratize this technology for smaller farms. Furthermore, achieving seamless interoperability between the myriad of IoT devices, platforms, and autonomous vehicles from different manufacturers is a crucial technical challenge that must be addressed through industry-wide standardization. The role of machine learning will also be pivotal; future efforts should focus on refining these algorithms for even more accurate predictive analytics for disease outbreaks, yield forecasting, and optimal resource scheduling. Finally, ensuring the resilience and reliability of these systems under varying and sometimes harsh field conditions is paramount for building trust among the farming community. By systematically addressing these challenges, the agricultural technology community can mature this promising integration, ultimately contributing substantially to the global goals of achieving sustainable agriculture and long-term food security for a growing population.

DECLARATIONS

Ethical Approval

We affirm that this manuscript is an original work, has not been previously published, and is not currently under consideration for publication in any other journal or conference proceedings. All authors have reviewed and approved the manuscript, and the order of authorship has been mutually agreed upon.

Funding

There is no funding

Availability of data and material

All of the data obtained or analyzed during this study is included in the report that was submitted.

Conflicts of Interest

The authors declare that they have no financial or personal interests that could have influenced the research and findings presented in this paper. The authors alone are responsible for the content and writing of this article.

Authors' contributions

All authors contributed equally in the preparation of this manuscript.

REFERENCES

- [1] Ayaz, M., Ammad-Uddin, M., Sharif, Z., Mansour, A. and Aggoune, E.H.M., **2019**. Internet-of-Things (IoT)-based smart agriculture: Toward making the fields talk. *IEEE Access*, 7, pp.129551-129583.
- [2] Boursianis, A.D., Papadopoulou, M.S., Diamantoulakis, P., Liopa-Tsakalidi, A., Barouchas, P., Salahas, G. and Goudos, S.K., **2022**. Internet of things (IoT) and agricultural unmanned aerial vehicles (UAVs) in smart farming: A comprehensive review. *Internet of Things*, 18, p.100187.
- [3] Kim, W.S., Lee, W.S. and Kim, Y.J., **2020**. A review of the applications of the internet of things (IoT) for agricultural automation. *Journal of Biosystems Engineering*, 45, pp.385-400.
- [4] Rai, H.M., Gupta, D., Mishra, S. and Sharma, H., **2021**. Agri-Bot: IoT Based Unmanned Smart Vehicle for

- Multiple Agriculture Operation. In **2021 International Conference on Simulation, Automation & Smart Manufacturing (SASM)** (pp. 1-6). IEEE.
- [5] Dhanaraju, M., Chenniappan, P., Ramalingam, K., Pazhanivelan, S. and Kaliaperumal, R., **2022**. Smart farming: Internet of Things (IoT)-based sustainable agriculture. *Agriculture*, 12(10), p.1745.
- [6] Narasimman, D.S., Reddy, M.A., Bhargav, P.S., Mahathi, Reddy, S.M. and Vijyalaxmi, K., **2022**. IoT Based Smart Agriculture And Automatic Seed Sowing Robot. *Journal of Engineering Sciences*, 13(7), pp.513-548.
- [7] Kumar, R., Sinwar, D., Pandey, A., Tadele, T., Singh, V. and Raghuwanshi, G., **2022**. IoT enabled technologies in smart farming and challenges for adoption. In *Internet of Things and Analytics for Agriculture*, Volume 3 (pp. 141-164). Springer, Singapore.
- [8] Rajak, P., Ganguly, A., Adhikary, S. and Bhattacharya, S., **2023**. Internet of Things and smart sensors in agriculture: Scopes and challenges. *Journal of Agriculture and Food Research*, 14, p.100776.
- [9] Singh, G. and Yogi, K.K., **2022**. Internet of things-based devices/robots in agriculture 4.0. In *Sustainable Communication Networks and Application: Proceedings of ICSCN 2021* (pp. 87-102). Springer Nature Singapore.
- [10] Sinha, B.B. and Dhanalakshmi, R., **2022**. Recent advancements and challenges of Internet of Things in smart agriculture: A survey. *Future Generation Computer Systems*, 126, pp.169-184.
- [11] Vasanti Venkateshwar, S., Mohiddin, M., Vineeta and Manek, A.S., **2021**. Innovative Farming: An Automated IoT Based Multipurpose Vehicle for Farmers. In *Data Science and Computational Intelligence: Sixteenth International Conference on Information Processing, ICInPro 2021, Bengaluru, India, October 22–24, 2021, Proceedings 16* (pp. 501-512). Springer International Publishing.
- [12] Patil, D.D., Singh, A.K., Shrivastava, A. and Bairagi, D., **2022**. IOT Sensor-Based Smart Agriculture Using Agro-robot. In *IoT Based Smart Applications* (pp. 345-361). Springer International Publishing.
- [13] Hassan, S.I., Alam, M.M., Illahi, U., Al Ghamdi, M.A., Almotiri, S.H. and Su'ud, M.M., **2021**. A systematic review on monitoring and advanced control strategies in smart agriculture. *IEEE Access*, 9, pp.32517-32548.
- [14] United Nations, Department of Economic and Social Affairs, Population Division, **2019**. World Population Prospects 2019: Highlights (ST/ESA/SER.A/423).
- [15] Baazzouz, A. and Dabounou, J., **2025**. Interpretability of neural network using layer conductance analysis for the concept detection. *Journal of Engineering and Applied Science*, 72(1), p.152.
- [16] Maheshwari, R.U. and Paulchamy, B., **2025**. Innovative graded-index PCF-based SPR sensor for advanced deepfake detection and real-time media integrity analysis. *Plasmonics*, 20(5), pp.2977-2996.
- [17] Mekonnen, Y., Burton, L., Sarwat, A. and Bhansali, S., **2021**. IoT-based smart agriculture: a comprehensive review. *IEEE Instrumentation & Measurement Magazine*, 24(3), pp.36-53.
- [18] Goap, A., Sharma, D., Shukla, A.K. and Krishna, C.R., **2018**. An IoT based smart irrigation management system using Machine learning and open source technologies. *Computers and Electronics in Agriculture*, 155, pp.41-49.
- [19] Bekhti, M., Achir, N. and Boussetta, K., **2023**. A comprehensive survey on the application of unmanned aerial vehicles in precision agriculture. *Computers and Electronics in Agriculture*, 214, p.108316.
- [20] Adão, T., Hruška, J., Pádua, L., Bessa, J., Peres, E., Morais, R. and Sousa, J.J., **2017**. Hyperspectral imaging: A review on UAV-based sensors, data processing and applications for agriculture and forestry. *Remote Sensing*, 9(11), p.1110.
- [21] Pedersen, S.M., Fountas, S. and Blackmore, S., **2021**. Agricultural robots—applications and economic perspectives. In *Robotics and Automation for Improving Agriculture* (pp. 1-20). Burleigh Dodds Science Publishing.
- [22] Vougioukas, S.G., **2019**. Agricultural robotics. *Annual Review of Control, Robotics, and Autonomous Systems*, 2, pp.365-392.
- [23] Javaid, M., Haleem, A., Singh, R.P. and Suman, R., **2022**. Enhancing smart farming through the applications of Agriculture 4.0 technologies. *International Journal of Intelligent Networks*, 3, pp.150-164.
- [24] Abu, N.S., Bukhari, W.M., Ong, C.H., Kassim, A.M., Izzuddin, T.A., Sukhaimie, M.N. and Rasid, A.F.A., **2022**. Internet of things applications in precision agriculture: A review. *Journal of Robotics and Control (JRC)*, 3(3), pp.338-347.
- [25] Marcu, I.M., Suci, G., Balaceanu, C.M. and Banaru, A., **2019**. IoT based system for smart agriculture. In **2019 11th International Conference on Electronics, Computers and Artificial Intelligence (ECAI)** (pp. 1-4). IEEE.

- [26] Tzounis, A., Katsoulas, N., Bartzanas, T. and Kittas, C., **2017**. Internet of Things in agriculture, recent advances and future challenges. *Biosystems Engineering*, 164, pp.31-48.
- [27] Wolfert, S., Sorensen, C.A. and Goense, D., **2022**. Digital twin applications in agriculture: A review. *Smart Agricultural Technology*, 2, p.100043.
- [28] McBratney, A., Whelan, B., Ancev, T. and Bouma, J., **2005**. Future directions of precision agriculture. *Precision Agriculture*, 6(1), pp.7-23.
- [29] [29] Liakos, K.G., Busato, P., Moshou, D., Pearson, S. and Bochtis, D., **2018**. Machine learning in agriculture: A review. *Sensors*, 18(8), p.2674.
- [30] Zhang, N., Wang, M. and Wang, N., **2002**. Precision agriculture—a worldwide overview. *Computers and Electronics in Agriculture*, 36(2-3), pp.113-132.
- [31] Shafi, U., Mumtaz, R., García-Nieto, J., Hassan, S.A., Zaidi, S.A.R. and Iqbal, N., **2019**. Precision agriculture techniques and practices: From considerations to applications. *Sensors*, 19(17), p.3796.
- [32] Lowenberg-DeBoer, J. and Erickson, B., **2019**. Setting the record straight on precision agriculture adoption. *Agronomy Journal*, 111(4), pp.1552-1569.
- [33] Ray, P.P., **2017**. Internet of things for smart agriculture: Technologies, practices and future direction. *Journal of Ambient Intelligence and Smart Environments*, 9(4), pp.395-420.
- [34] Ji, W., Zhao, D., Cheng, F. and Xu, B., **2022**. Optimal deployment of sensors in IoT-based smart agriculture using wireless sensor networks. *Computers and Electronics in Agriculture*, 198, p.107087.
- [35] Balafoutis, A., Beck, B., Fountas, S., Vangeyte, J., Van der Wal, T., Soto, I. and Eory, V., **2017**. Precision agriculture technologies positively contributing to GHG emissions mitigation, farm productivity and economics. *Sustainability*, 9(8), p.1339.
- [36] Moghimi, A., Yang, C. and Miller, M.E., **2020**. A review of machine learning approaches to plant disease detection. *Frontiers in Plant Science*, 11, p.601.
- [37] Sutton, M.A., Oenema, O., Erisman, J.W., Leip, A., van Grinsven, H. and Winiwarter, W., **2011**. Too much of a good thing. *Nature*, 472(7342), pp.159-161.
- [38] Weiss, M., Jacob, F. and Duveiller, G., **2020**. Remote sensing for agricultural applications: A meta-review. *Remote Sensing of Environment*, 236, p.111402.
- [39] Grisso, R.D., Alley, M.M., McClellan, P. and Brann, D.E., **2011**. Precision farming tools: Soil electrical conductivity. *Virginia Cooperative Extension*, 442-508.
- [40] Long, T.B., Blok, V. and Coninx, I., **2016**. Barriers to the adoption and diffusion of technological innovations for climate-smart agriculture in Europe: A systematic review. *Agricultural Systems*, 151, pp.163-174.
- [41] United Nations, **2015**. *Transforming our world: The 2030 agenda for sustainable development*. Department of Economic and Social Affairs.
- [42] Finger, R., Swinton, S.M., El Benni, N. and Walter, A., **2019**. Precision farming at the nexus of agricultural production and the environment. *Annual Review of Resource Economics*, 11, pp.313-335.
- [43] Gebbers, R. and Adamchuk, V.I., **2010**. Precision agriculture and food security. *Science*, 327(5967), pp.828-831.
- [44] Van Klompenburg, T., Kassahun, A. and Catal, C., **2020**. Crop yield prediction using machine learning: A systematic literature review. *Computers and Electronics in Agriculture*, 177, p.105709.
- [45] Shearer, S.A., **2000**. The role of management information systems in precision agriculture. *Computers and Electronics in Agriculture*, 28(3), pp.227-240.
- [46] Rose, D.C., Wheeler, R., Winter, M., Lobley, M. and Chivers, C.A., **2021**. Agriculture 4.0: Making it work for people, production, and the planet. *Land Use Policy*, 100, p.104933.